

A B C D E F


1

2

3

4

5



Undersized Diameter for Roll Thread,
Ø.677 min.

- Available in the Following Grades:
- F1554 Gr. 55
 - F1554 Gr. 55 Hot Dip Galv.
 - F1554 Gr. 105
 - 304 Stainless

UNLESS OTHERWISE SPECIFIED				DRAWN: Alan Harris		12/21/2021		Alexander Screw Products, Inc.		8750 Pendleton Pike Indianapolis, IN 46226	
DIMENSIONS ARE IN INCHES				MATERIAL		CHECK:		TITLE:		REV.	
.X	.XX	.XXX	ANGLE	SAE 304				AS075048S			
±	±	±	± 0.5°	FINISH		ENGR:		MFG:		REVISION BY:	
	125 ✓			Stainless		12/21/2021				CUSTOMER:	
DIMENSIONING & TOLERANCING PER ASME Y14.5-2009 ALL DIMENSIONS IN INCHES [MM] BEFORE / AFTER SURFACE TREATMENT REMOVE ALL BURS AND SHARP EDGES THREADS: EXT CLASS 2A, INT 2B PROTECTIVE WRAP OR EQUIV. IDENTIFY PART ON WRAP OR EQUIV.						REVISION BY:		SCALE		SHEET	
						CUSTOMER:		C		Anchor Bolt Print	
								WT		1 OF 1	
								N/A			

Anchor Bolt Print

P/N